

Bayfield Series

DIRECT/INDIRECT

Features

- White housing with reflector
- Lens or perforated metal basket
- Direct/indirect light distribution
- UL Listed

Specifications

- Ballasts are thermally protected Class P, non-PCB and UL listed. Electronic ballasts are sound rated "A".
- Housings are formed from cold rolled steel and painted with a high-gloss, baked white enamel finish after multi-stage cleaning and a phosphate coating to inhibit rust, has been applied.
- Fixture is designed for ceiling mounting
- Equipped with a reflector and 3 different shielding options for a mix of directional illumination.
- Lens or perforated metal basket, easily removed from either side.

Application

- Commercial or residential
- Offices
- General lighting

Options

- 120 volt
- 277 volt
- Multi-volt (120-277v, 50 or 60 Hertz)
- 0 Degree F
- Dimming
- THD less than 10% - instant start
- THD less than 10% - rapid start
- Program Start
- Low Watt (Low Ballast Factor)
- High Light output (High Ballast Factor)
- Dual level wiring



Shielding Options

- Ribbed acrylic lens
- Prismatic acrylic lens
- Perforated metal basket

Accessories

- Emergency battery pack
- Fuses
- Radio interference filters
- Uplite reflectors

Catalog Number	Type