

Features

- Square metal sided surface mount
- Two sizes with many lamp configurations
- Many diffuser options
- UL Listed

Specifications

- Ballasts are thermally protected Class P, non-PCB and UL listed. Electronic ballasts are sound rated "A".
- Housings are formed from cold rolled steel and post painted with a high-gloss, baked white enamel finish after multi-stage cleaning and a phosphate coating to inhibit rust, has been applied.
- Fixture is designed for ceiling mounting and is available in many sizes and lamp configurations.
- Standard diffuser is 100% virgin acrylic. Many others available upon request.
- Door has mitered corners and hinges from either side.
* See 810 and 824 for similar fixtures.

Application

- Commercial or residential
- Schools
- Offices
- General lighting

Options

- 120 volt
- 277 volt
- Multi-volt (120-277v, 50 or 60 Hertz)
- 0 Degree F
- Dimming
- THD less than 10% - instant start
- THD less than 10% - rapid start
- Program Start
- Low Watt (Low Ballast Factor)
- High Light output (High Ballast Factor)
- Dual level wiring



Diffusers

DA
DJ
DK
DM
DR
DL

See accessories page for details

Accessories

- Aluminum regressed doors
- Tamper resistant/rough service
- Emergency battery pack
- Gasketing

Catalog Number	Type